



## Copper Tube Lugs 1.5mm<sup>2</sup>:

### Description:

Tin plated copper tube terminals with a cable entry size of 1.5mm<sup>2</sup>.

Supplied with an inspection hole to ensure the conductor is fully inserted before crimping.

A bell mouth entry also ensures a smooth transition from lug to cable, avoiding problems such as chafing where the component is subject to vibration.

### Technical Specification:

Cable Entry: 1.5mm<sup>2</sup>

Material: Copper (99.9%), Tin (0.01%)

Specifications: Manufactured from seamless copper tube to BS2871/C106  
Fully Compliant with BSEN 61238-1-2003 & IEC 61238-2003.  
Internal barrel diameter suits standard cables as defined in BS6360.



### Dimensions:

Product Code	Conductor Size mm <sup>2</sup>	Stud Size	Length (L)	Width (W)	Inside Ø (D)	Hole Ø (dØ)
T1.5-3	1.5mm <sup>2</sup>	M3	17.0	5.5	1.8	3.2
T1.5-3	1.5mm <sup>2</sup>	M4	19.5	8.0	1.9	4.3
T1.5-3	1.5mm <sup>2</sup>	M5	20.4	8.0	1.9	5.3

All dimensions and sizes are displayed in millimetres unless otherwise stated.

